

COMPRESSOR DEFINITION

Designation	EM TS2125U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300757

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure (Curves until T.Evap -10°C / Peak 60°C)		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Fan	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Fan	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO22	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-34	
3 Start capacitor	43-53(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM276NFBYY-53	
6 Start winding resistance		[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance		[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	8.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1031	260	302	197	1.21	3.07	5.23	1.32	1.53

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	757	191	222	135	1.01	2.24	5.58	1.41	1.63
-30 (-22)	969	244	284	150	1.05	2.87	6.46	1.63	1.89
-25 (-13)	1219	307	357	165	1.09	3.62	7.41	1.87	2.17
-20 (- 4)	1509	380	442	179	1.14	4.50	8.45	2.13	2.48
-15 (+ 5)	1843	465	540	193	1.19	5.52	9.59	2.42	2.81
-10 (+14)	2223	560	651	205	1.24	6.69	10.84	2.73	3.18

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	670	169	196	141	1.02	1.98	4.75	1.20	1.39
-30 (-22)	859	217	252	158	1.07	2.55	5.42	1.37	1.59
-25 (-13)	1084	273	318	176	1.13	3.22	6.14	1.55	1.80
-20 (- 4)	1345	339	394	194	1.19	4.01	6.91	1.74	2.02
-15 (+ 5)	1646	415	482	212	1.26	4.93	7.74	1.95	2.27
-10 (+14)	1990	502	583	230	1.33	5.99	8.65	2.18	2.54

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	575	145	169	146	1.03	1.70	3.96	1.00	1.16
-30 (-22)	743	187	218	165	1.09	2.20	4.51	1.14	1.32
-25 (-13)	941	237	276	186	1.16	2.80	5.05	1.27	1.48
-20 (- 4)	1173	296	344	208	1.24	3.50	5.62	1.42	1.65
-15 (+ 5)	1442	363	423	231	1.33	4.32	6.22	1.57	1.82
-10 (+14)	1750	441	513	255	1.42	5.26	6.85	1.73	2.01

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	480	121	141	149	1.04	1.42	3.20	0.81	0.94
-30	(-22)	625	157	183	170	1.11	1.85	3.68	0.93	1.08
-25	(-13)	798	201	234	194	1.20	2.37	4.13	1.04	1.21
-20	(- 4)	1000	252	293	220	1.29	2.98	4.56	1.15	1.34
-15	(+ 5)	1237	312	362	249	1.40	3.70	4.99	1.26	1.46
-10	(+14)	1508	380	442	278	1.52	4.54	5.42	1.37	1.59

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal AMEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		