

COMPRESSOR DEFINITION

Designation	NT 6226GKV
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	923AA02

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	22.37	[cm ³] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	16.65	[kg] (36.71 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA403C-123	
3 Start capacitor	130-156(250)	[µF(VAC minimum)]
4 Run capacitor	20(400)	[µF(VAC minimum)]
5 Motor protection	T0828/C9	
6 Start winding resistance	7.56	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.22	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	37.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5978	1506	1752	980	4.78	52.62	6.10	1.54	1.79

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4634	1168	1358	764	3.82	35.17	6.06	1.53	1.78
-15	(+ 5)	5769	1454	1690	831	4.12	44.22	6.96	1.75	2.04
-10	(+14)	7159	1804	2098	898	4.41	55.33	7.98	2.01	2.34
-5	(+23)	8794	2216	2577	966	4.71	68.64	9.10	2.29	2.67
0	(+32)	10663	2687	3124	1035	5.03	84.27	10.29	2.59	3.02
+5	(+41)	12754	3214	3737	1106	5.35	102.37	11.52	2.90	3.38
+10	(+50)	15058	3795	4412	1180	5.69	123.06	12.77	3.22	3.74

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3823	964	1120	821	4.07	33.01	4.66	1.17	1.36
-15	(+ 5)	4793	1208	1404	901	4.42	41.81	5.32	1.34	1.56
-10	(+14)	5972	1505	1750	980	4.77	52.58	6.09	1.53	1.78
-5	(+23)	7350	1852	2154	1059	5.13	65.44	6.94	1.75	2.03
0	(+32)	8916	2247	2613	1138	5.48	80.55	7.84	1.97	2.30
+5	(+41)	10659	2686	3123	1218	5.85	98.02	8.76	2.21	2.57
+10	(+50)	12568	3167	3683	1299	6.23	117.99	9.67	2.44	2.83

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3077	775	902	869	4.30	31.26	3.55	0.89	1.04
-15	(+ 5)	3879	977	1137	967	4.73	39.85	4.01	1.01	1.17
-10	(+14)	4845	1221	1420	1062	5.15	50.32	4.55	1.15	1.33
-5	(+23)	5963	1503	1747	1156	5.58	62.79	5.16	1.30	1.51
0	(+32)	7224	1820	2117	1249	6.00	77.41	5.79	1.46	1.70
+5	(+41)	8617	2171	2525	1342	6.44	94.30	6.43	1.62	1.89
+10	(+50)	10130	2553	2968	1435	6.88	113.60	7.04	1.78	2.06

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		