

COMPRESSOR DEFINITION

Designation	EM X4125U
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513301823

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low-Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	5.89	[cm ³] (0.359 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO22	
4 Weight (with oil charge)	8.5	[kg] (18.74 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	QL2-9.1	
3 Start capacitor	189-227(220)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	4TM762NFBZZ-53	
6 Start winding resistance	6.76	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.17	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	21.36	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	3.76	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	4.33	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
1210	305	355	207	2.40	3.60	5.85	1.47	1.71	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	749	189	219	140	2.08	2.21	5.39	1.36	1.58	
-30 (-22)	1001	252	293	160	2.26	2.97	6.20	1.56	1.82	
-25 (-13)	1286	324	377	180	2.44	3.83	7.10	1.79	2.08	
-20 (- 4)	1604	404	470	197	2.60	4.79	8.09	2.04	2.37	
-15 (+ 5)	1954	492	573	213	2.75	5.85	9.19	2.32	2.69	
-10 (+14)	2337	589	685	226	2.88	7.03	10.41	2.62	3.05	
-5 (+23)	2753	694	807	235	2.97	8.32	11.79	2.97	3.45	
0 (+32)	3201	807	938	240	3.02	9.73	13.32	3.36	3.90	

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	682	172	200	144	2.21	2.02	4.78	1.21	1.40	
-30 (-22)	908	229	266	166	2.38	2.69	5.47	1.38	1.60	
-25 (-13)	1173	296	344	188	2.57	3.49	6.21	1.57	1.82	
-20 (- 4)	1477	372	433	210	2.75	4.41	7.02	1.77	2.06	
-15 (+ 5)	1820	459	533	230	2.93	5.45	7.90	1.99	2.31	
-10 (+14)	2203	555	645	248	3.10	6.63	8.88	2.24	2.60	
-5 (+23)	2625	661	769	263	3.25	7.94	9.97	2.51	2.92	
0 (+32)	3086	778	904	275	3.36	9.38	11.20	2.82	3.28	

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	618	156	181	145	2.22	1.83	4.23	1.07	1.24	
-30 (-22)	820	207	240	169	2.41	2.43	4.85	1.22	1.42	
-25 (-13)	1067	269	313	195	2.61	3.17	5.50	1.39	1.61	
-20 (- 4)	1360	343	398	221	2.83	4.06	6.17	1.55	1.81	
-15 (+ 5)	1698	428	498	247	3.06	5.09	6.89	1.74	2.02	
-10 (+14)	2083	525	610	271	3.29	6.27	7.68	1.94	2.25	
-5 (+23)	2513	633	736	294	3.50	7.60	8.56	2.16	2.51	
0 (+32)	2989	753	876	314	3.70	9.09	9.53	2.40	2.79	

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		