

### COMPRESSOR DEFINITION

Designation	NE U6214U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	862GA51

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	12.11	[cm <sup>3</sup> ] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.4	[kg] (22.93 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4L3C-566	
3 Start capacitor	53-64(330)	[µF(VAC minimum)]
4 Run capacitor	7(400)	[µF(VAC minimum)]
5 Motor protection	T0874/G9	
6 Start winding resistance	18.83	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.14	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	19.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - CE - UKCA - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5741	1447	1682	611	3.06	19.65	9.40	2.37	2.75

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2587	652	758	349	2.02	7.30	7.40	1.87	2.17
-15	(+ 5)	3189	804	934	376	2.10	9.04	8.48	2.14	2.49
-10	(+14)	3905	984	1144	402	2.18	11.11	9.72	2.45	2.85
-5	(+23)	4734	1193	1387	427	2.28	13.53	11.09	2.80	3.25
0	(+32)	5677	1431	1664	451	2.37	16.32	12.60	3.18	3.69
+5	(+41)	6734	1697	1973	473	2.47	19.48	14.24	3.59	4.17
+10	(+50)	7903	1992	2316	494	2.58	23.03	15.98	4.03	4.68

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2293	578	672	379	2.08	7.00	6.05	1.52	1.77
-15	(+ 5)	2841	716	832	412	2.19	8.70	6.89	1.74	2.02
-10	(+14)	3487	879	1022	444	2.31	10.73	7.85	1.98	2.30
-5	(+23)	4233	1067	1240	475	2.43	13.09	8.91	2.24	2.61
0	(+32)	5079	1280	1488	505	2.56	15.80	10.06	2.53	2.95
+5	(+41)	6023	1518	1765	534	2.69	18.87	11.29	2.84	3.31
+10	(+50)	7067	1781	2071	562	2.84	22.32	12.59	3.17	3.69

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1962	494	575	401	2.20	6.54	4.90	1.23	1.43
-15	(+ 5)	2450	617	718	442	2.35	8.20	5.55	1.40	1.63
-10	(+14)	3024	762	886	483	2.50	10.17	6.27	1.58	1.84
-5	(+23)	3683	928	1079	523	2.66	12.45	7.05	1.78	2.06
0	(+32)	4427	1116	1297	562	2.83	15.07	7.88	1.99	2.31
+5	(+41)	5255	1324	1540	600	3.01	18.03	8.75	2.21	2.56
+10	(+50)	6169	1555	1808	638	3.19	21.35	9.66	2.43	2.83

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		