

### COMPRESSOR DEFINITION

Designation	VEM T404U
Nominal Voltage/Frequency	230 V 40-150 Hz
Engineering Number	513903040

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	230 / 40-150	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure (Light Commercial / Peak 65°C)		
4.1 Evaporating temperature range	-40°C to 0°C	(-40°F to 32°F)	
5 Motor type	BPM		
6 Starting torque	LST/HST - Low/High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static/Fan	103 to 140 V	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static/Fan	103 to 140 V	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3+	[hp]
2 Displacement	4.25	[cm <sup>3</sup> ] (0.259 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	220	[ml] (7.44 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO22	
4 Weight (with oil charge)	7.18	[kg] (15.83 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 40-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	CF03B01 N XX XX	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	INVERTER CF03B01 N X	
6 Start winding resistance	13.65	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.65	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	2.80/2.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	2.00/2.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	2.00/2.00	[A] - Measured according to UL 984
11 Approval boards certification	TUV - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@115V1200RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
326	82	95	61	0.96	0.97	5.33	1.34	1.56

TEST CONDITIONS: <b>@115V1200RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	58	0.92	0.98	5.66	1.43	1.66

TEST CONDITIONS: <b>@115V1600RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
406	102	119	71	1.09	1.21	5.72	1.44	1.68

TEST CONDITIONS: <b>@115V1600RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
414	104	121	70	1.07	1.23	5.94	1.50	1.74

TEST CONDITIONS: <b>@115V2000RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
504	127	148	86	1.29	1.50	5.86	1.48	1.72

TEST CONDITIONS: <b>@115V2000RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
519	131	152	85	1.28	1.54	6.08	1.53	1.78

### E - PERFORMANCE - CURVES

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@115V3000RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
754	190	221	126	1.83	2.24	6.00	1.51	1.76

TEST CONDITIONS: <b>@115V3000RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
777	196	228	126	1.83	2.31	6.14	1.55	1.80

TEST CONDITIONS: <b>@115V3600RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
883	223	259	148	2.12	2.63	5.96	1.50	1.75

TEST CONDITIONS: <b>@115V3600RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
914	230	268	150	2.13	2.72	6.09	1.53	1.78

TEST CONDITIONS: <b>@115V4500RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1116	281	327	191	2.66	3.32	5.84	1.47	1.71

TEST CONDITIONS: <b>@115V4500RPM</b>			<b>ASHRAELBP32</b> <b>Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1158	292	339	194	2.69	3.45	5.96	1.50	1.75

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		