

### COMPRESSOR DEFINITION

Designation	NE U6217U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	863SA51

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm <sup>3</sup> ] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3AN3C-575	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	12.5(400)	[µF(VAC minimum)]
5 Motor protection	MRA38173-3261	
6 Start winding resistance	14.95	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	21.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3609	909	1058	518	2.47	12.99	6.97	1.76	2.04

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2766	697	811	407	1.98	8.97	6.78	1.71	1.99
-15	(+ 5)	3381	852	991	439	2.11	11.02	7.72	1.94	2.26
-10	(+14)	4123	1039	1208	468	2.24	13.52	8.81	2.22	2.58
-5	(+23)	4992	1258	1463	497	2.37	16.48	10.05	2.53	2.94
0	(+32)	5988	1509	1755	524	2.49	19.94	11.42	2.88	3.35
+5	(+41)	7111	1792	2084	550	2.61	23.91	12.93	3.26	3.79
+10	(+50)	8362	2107	2450	575	2.72	28.44	14.54	3.67	4.26

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2402	605	704	439	2.12	8.53	5.48	1.38	1.61
-15	(+ 5)	2952	744	865	479	2.30	10.55	6.17	1.55	1.81
-10	(+14)	3611	910	1058	517	2.46	12.99	6.97	1.76	2.04
-5	(+23)	4379	1103	1283	554	2.63	15.88	7.90	1.99	2.31
0	(+32)	5257	1325	1540	589	2.78	19.24	8.92	2.25	2.61
+5	(+41)	6244	1574	1830	623	2.94	23.10	10.03	2.53	2.94
+10	(+50)	7341	1850	2151	655	3.08	27.50	11.23	2.83	3.29

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2035	513	596	465	2.24	8.05	4.37	1.10	1.28
-15	(+ 5)	2510	633	736	516	2.47	9.99	4.87	1.23	1.43
-10	(+14)	3077	775	902	565	2.69	12.34	5.45	1.37	1.60
-5	(+23)	3736	941	1095	612	2.90	15.11	6.11	1.54	1.79
0	(+32)	4486	1131	1315	657	3.11	18.34	6.84	1.72	2.00
+5	(+41)	5329	1343	1562	700	3.31	22.05	7.62	1.92	2.23
+10	(+50)	6264	1579	1836	741	3.50	26.27	8.45	2.13	2.47

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		