





+ 24%*
COOLING CAPACITY



UP TO 30%* LESS WEIGHT



+ 10%*
MORE EFFICIENCY



LOWER NOISE LEVELOn the system



10%* LESS HEIGHT



ROBUSTNESS AND RELIABILITY

*Comparison with other models in the market and based on internal tests.



Discover everything that our digital tools can do for your business



A channel for the refrigeration market: Join us at: **refrigerationclub.com**



APPLICATIONS







DISPLAY CABINET



REFRIGERATED **ISLAND**



REACH IN

| MODELS GENERAL DATA* | | | | | | | | | | | |
|----------------------|------------|--|-------|---------------|--------------|-----------------------|--------------------|--------------|--------------------|--------------|-------------------|
| Develop Wave | MODEL | NOMINAL VOLTAGE [V] / FREQUENCY [Hz] | MOTOR | DISP. [cc] | REFR. GAS | ENV. RANGE [°C] | 50Hz | | 60Hz | | TEST |
| | | | | | | | COOLING CAP [W] | COP [W/W] | COOLING CAP [W] | COP [W/W] | TEST CONDITION |
| 0 | NEX4160UA | 115-127V 60Hz | CSCR | 14.4 | R290 | -40 to 0 | - | - | 675 | 1.36 | ARILBP |
| 0 | NEX4170UA | 115-127V 60Hz | CSCR | 16.8 | R290 | -40 to 0 | - | - | 804 | 1.36 | ARILBP |
| 1 | NEX4180UA | 115-127V 60Hz | CSCR | 18.7 | R290 | -40 to 0 | - | - | 895 | 1.36 | ARILBP |
| 1 | NEX2180UA | 220-240V 50Hz | CSCR | 18.7 | R290 | -40 to -10 | 935 | 1.62 | - | - | ASHRAELBP32 |
| 1 | NEX6222UA | 220-240V 50Hz | CSCR | 18.7 | R290 | -20 to 10 | 1317 | 2.2 | - | - | EN12900MBP |
| 1 | NEX6225UA | 220-240V 50Hz | CSCR | 21 | R290 | -20 to 10 | 1572 | 2.08 | - | - | EN12900MBP |
| 4 | NEX2190UA | 220-240V 50Hz | CSCR | 21 | R290 | -40 to -10 | 1040 | 1.6 | - | - | ASHRAELBP32 |
| 2 | NEX6221UA | 115-127V 60Hz | CSCR | 16.8 | R290 | -20 to 10 | - | - | 1560 | 1.91 | ARIMBP |
| 2 | NEU2168GKA | 220-240V 50Hz | CSCR | 13.5 | R404A | -40 to -10 | 760 | 1.34 | - | - | ASHRAELBP32 |
| 2 | NEU2178GKA | 220-240V 50Hz | CSCR | 15.7 | R404A | -40 to -10 | 900 | 1.47 | - | - | ASHRAELBP32 |
| 2 | NEU2183GKA | 220-240V 50Hz | CSCR | 16.8 | R404A | -40 to -10 | 967 | 1.48 | - | - | ASHRAELBP32 |
| 3 | NEU6217UA | 220-240V 50Hz | CSIR | 14.3 | R290 | -20 to 10 | 1055 | 1.92 | - | - | EN12900MBP |
| 3 | NEX6217UA | 220-240V 50Hz | CSCR | 14.3 | R290 | -20 to 10 | 1078 | 2.09 | - | - | EN12900MBP |
| 3 | NEU2168UA | 220-240V 50Hz | CSIR | 16.8 | R290 | -40 to -10 | 788 | 1.53 | - | - | ASHRAELBP32 |
| 3 | NEX2178UA | 220-240V 50Hz | CSCR | 18.7 | R290 | -40 to -10 | 935 | 1.53 | - | - | ASHRAELBP32 |

DIGITAL TOOLS



Free App available in 10 languages, includes several tools for the professional technician.

FIND INSIDE:

- Products Catalog
- · Cross Reference
- Distributor Locator
- Unit Converter
- Troubleshooting
- Refrigerant Slider

Download available for iOS and Android









Embraco offers digital tools and services focused on providing support for refrigeration professionals on their daily routine.



PRODUCT SOFTWARE SELECTOR

Find the right product for your application and detailed datasheets for compressors and condensing units. You can also download the software and use it offline.

Access: products.embraco.com



REFRIGERATION CLUB

Join the club and stay informed of market trends, technical tips and watch exclusive videos. Conect with us at: refrigerationclub.com

