

ROBUSTNESS IN A SMALLER DESIGN

# NEX

More **cooling capacity** for **food retail** and **food service** equipments



EXTENSION OF  
NE PLATFORM  
UP TO 21CC



+ 24%\*  
**COOLING CAPACITY**



**ENVIRONMENTALLY FRIENDLY**

Uses R290 natural refrigerant with no impact on the ozone layer (GWP3)



+ 10%\*  
**MORE EFFICIENCY**



**LOWER NOISE LEVEL**

On the system



10%\* **LESS HEIGHT**  
AND UP TO 30%\*  
**LESS WEIGHT**



**ROBUSTNESS AND RELIABILITY**

*\*Comparison with other models in the market and based on internal tests.*

## MAIN APPLICATIONS



ICE MACHINE



DISPLAY CABINET



REFRIGERATED ISLAND



REACH IN

## TECHNICAL DATA

MODEL	NOMINAL VOLTAGE [V] / FREQUENCY [Hz]	HP	DISP. [cc]	MOTOR	REFRIG	ENV. RANGE [°C]	TEST CONDITION (rated point)	50Hz		60Hz	
								CAP [W]	COP [W/W]	CAP [W]	COP [W/W]
<b>NEX2180UB</b>	220-240V 50Hz	1	18,7	CSCR	R290	-40 to -10	ASHRAE LBP	929	1,59	-	-
<b>NEU2178U</b>	220-240V 50Hz	1	18,7	CSCR	R290	-40 to -10	ASHRAE LBP	905	1.52		
<b>NEX4170UA</b>	115-127V 60Hz	1/2	16,8	CSCR	R290	-40 to 0	ARI LBP	-	-	789	1,34
<b>NEX4180UA</b>	115-127V 60Hz	1	18,7	CSCR	R290	-40 to 0	ARI LBP	-	-	891	1,31
<b>NEU2178GK</b>	220-240V 50Hz	1	16,8	CSCR	R404A	-40 to -10	EN12900 LBP	501	1,14	-	-
<b>NEU2183GKA</b>	220-240V 50Hz	1	16,8	CSCR	R404A	-40 to -10	EN12900 LBP	502	1,15	-	-
<b>NEU2170UA</b>	220-240V 50Hz	3/4	16,8	CSCR	R290	-40 to -10	ASHRAE LBP	820	1,54	-	-
<b>NEX6217UA</b>	220-240V 50Hz	3/4	14,3	CSCR	R290	-20 to 10	EN12900 MBP	1071	2,09	-	-
<b>NEX6225UA</b>	220-240V 50Hz	1	21	CSCR	R290	-20 to 10	EN12900 MBP	1612	2,07	-	-



Discover all that our digital solutions can do to support your business.  
Access: [embraco.com](http://embraco.com)