

NEX



A complete portfolio
for your commercial
refrigeration needs



+24% Cooling
Capacity



+7% Energy
Consumption Saving



+10% More
Efficiency



+30% Less
Weight



Lower Noise



Robustness

think ahead

The Latest-Generation NE Global Platform:
robustness in a smaller design.
From 17 up to 21cc in a reduced height.




Main Application
Professional Kitchen | Display Cases

embraco
Nidec

Check out the specifications of some models

Model	Applic.	Nominal Voltage [V] / Frequency [Hz]	HP	Disp. [cc]	Refrigerant	Motor	Env. Range [°C]	Test Condition (Rated Point)	50Hz		60Hz	
									Cap [W]	COP [W/W]	Cap [W]	COP [W/W]
NEU2168U	LBP	220-240 V 50 Hz	3/4	16.8	R290	CSCR	-40 to -10	ASHRAE LBP	788	1.53		
NEU2170UA	LBP	220-240V 50Hz	3/4	16.8	R290	CSCR	-40 to -10	ASHRAE LBP	820	1.54	-	-
NEX2180UA	LBP	220-240V 50Hz	1	18.7	R290	CSCR	-40 to -10	ASHRAE LBP	932	1.62	-	-
NEX2180UB	LBP	220-240V 50Hz	1	18.7	R290	CSCR	-40 to -10	ASHRAE LBP	929	1.59	-	-
NEX2190UA	LBP	220-240V 50Hz	1	21	R290	CSCR	-40 to -10	ASHRAE LBP	1032	1.59	-	-
NEU2178U	LBP	220-240 V 50 Hz	1	18.7	R290	CSCR	-40 to -10	ASHRAE LBP	905	1.52		
NEU6217U	MBP	220-240 V 50 Hz	3/4	14.28	R290	CSCR	-20 to 10	EN12900 MBP	1058	2.04		
NEX6217UA	MBP	220-240V 50Hz	3/4	14.3	R290	CSIR	-20 to 10	EN12900 MBP	1055	1.91	-	-
NEX6222UA	MBP	220-240V 50Hz	1	18.7	R290	CSCR	-20 to 10	EN12900 MBP	1429	2.14	-	-
NEX6225UA	MBP	220-240V 50Hz	1	21	R290	CSCR	-20 to 10	EN12900 MBP	1612	2.07	-	-
NEU6212GL*	MBP	220-240 V 50 Hz	1/2	8.77	R454C/R455A*	CSIR	-20 to 10	EN12900 MBP	611	1.65		
NEU6215GL*	MBP	220-240 V 50 Hz	3/4	12.11	R454C/R455A*	CSCR	-20 to 10	EN12900 MBP	871	1.77		

* Models under development.



Scan and discover
all the possibilities
of this product

embraco
Nidec