

### COMPRESSOR DEFINITION

Designation	<b>NE U6210U</b>
Nominal Voltage/Frequency	<b>208-230 V 60 Hz</b>
Engineering Number	<b>862FD45</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	208-230 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	8.77	[cm <sup>3</sup> ] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	11.56	[kg] (25.49 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA5AG3C-107	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	10(400)	[µF(VAC minimum)]
5 Motor protection	MRA38171-3265	
6 Start winding resistance	8.96	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.67	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	25.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1943	490	569	345	2.72	6.86	5.63	1.42	1.65
-15	(+ 5)	2369	597	694	368	2.77	8.42	6.44	1.62	1.89
-10	(+14)	2915	735	854	389	2.82	10.45	7.49	1.89	2.20
-5	(+23)	3582	903	1050	408	2.87	12.97	8.79	2.21	2.58
0	(+32)	4369	1101	1280	424	2.93	15.99	10.31	2.60	3.02
+5	(+41)	5277	1330	1546	438	3.00	19.55	12.06	3.04	3.53
+10	(+50)	6305	1589	1847	450	3.09	23.67	14.01	3.53	4.10

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1635	412	479	360	2.70	6.39	4.56	1.15	1.34
-15	(+ 5)	2008	506	588	390	2.79	7.90	5.16	1.30	1.51
-10	(+14)	2489	627	729	417	2.87	9.88	5.96	1.50	1.75
-5	(+23)	3079	776	902	442	2.94	12.35	6.95	1.75	2.04
0	(+32)	3778	952	1107	465	3.02	15.35	8.12	2.05	2.38
+5	(+41)	4586	1156	1344	485	3.10	18.89	9.46	2.38	2.77
+10	(+50)	5502	1387	1612	503	3.20	23.00	10.96	2.76	3.21

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1332	336	390	371	2.71	5.86	3.58	0.90	1.05
-15	(+ 5)	1646	415	482	407	2.81	7.29	4.05	1.02	1.19
-10	(+14)	2057	518	603	441	2.91	9.20	4.67	1.18	1.37
-5	(+23)	2565	646	752	472	3.00	11.62	5.44	1.37	1.59
0	(+32)	3171	799	929	500	3.08	14.57	6.34	1.60	1.86
+5	(+41)	3874	976	1135	526	3.17	18.08	7.36	1.86	2.16
+10	(+50)	4674	1178	1369	550	3.27	22.17	8.50	2.14	2.49

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		