

COMPRESSOR DEFINITION

Designation	EH U4160U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513307553

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium (Plus) Back Pressure		
4.1 Evaporating temperature range	-35°C to 5°C	(-31°F to 41°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	2/3+	[hp]
2 Displacement	14.16	[cm ³] (0.864 cu.in)
2.1 Bore [mm]	28.000	
2.2 Stroke [mm]	23.000	
3 Lubricant charge	270	[ml] (9.13 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	9.1	[kg] (20.06 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213515059	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	12(400)	[µF(VAC minimum)]
5 Motor protection	DRB210N52A*F	
6 Start winding resistance	14.88	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	6.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	19.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	4.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	5.00	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		