EM X S 60 H E R

- Basic type
- Product Generation
- Mechanical Kit (Embraco Internal Use)
- Compressor capacity in Btu/h - 60Hz - Check point divided by 10
- Refrigerant
- Efficiency level
- Electrical Equipment

Electrical Equipment

- **P** - PTC + Run Cap (optional)
- **R** - Relay
- **C** - PTC + Run Cap (mandatory)
- **S** - PTC + Run Cap + Start Cap
- **V** - PTC + Run Cap + Start Cap (optional)
- **X** - Relay + Start Cap (mandatory)

LST: P, R, C, S, V

HST: X

Efficiency level

- **N** - Standard efficiency (LBP)
- **J** - Intermediate efficiency (LBP)
- **E** - Improved efficiency 1st generation (LBP)
- **S** - Improved efficiency 2nd generation (LBP)
- **H** - Standard efficiency (L/M/HBP)
- **D** - Standard efficiency (HBP)
- **B** - Standard efficiency (M/HBP)

Refrigerant

- H - R 134a
- C - R 600a
- U - R 290
- □ - R 12

Mechanical Kit

- S - Standard Mechanical Kit

Product Generation

- □ - Standard Generation
- I - 1st Generation
- T - 2nd Generation
- U - 3rd Generation
- Y - 4th Generation
- Z - 5th Generation
- X - 6th Generation

Basic type

- Embraco mini compressor

REVISION - 06
DATE - 25/10/05