

VEM & VEH

新变频产品，中国制造
更低的能耗，更长的预期寿命
制冷设备的优先选择



高能效



低噪音



宽电压



快速制冷



环境友好



寿命更长



可出口欧盟地区
有符合VDE要求的外部PFC



变频板组合
有可用于较小冷量压缩机的变频板


主要应用



立式冷柜



立式展示柜



岛柜



立式饮料柜

压缩机技术参数

制冷剂	型号	应用	工况	排量	蒸发温度范围	测试工况	转速	制冷量	能效
R290	VEMT404U	L/MBP	1/3+	4,3	-40°C to 0°	ASHRAE LBP	1200 - 4500	108 - 354	1,93
	VEMT406U	L/MBP	1/2	6,4	-40°C to 0°	ASHRAE LBP	1600 - 4500	157 - 434	1,72
	VEHT409U	L/MBP	1/2+	9,0	-40°C to 0°	ASHRAE LBP	1600 - 4500	228 - 675	1,77
	VEHT413U	L/MBP	1	12,7	-40°C to 0°	ASHRAE LBP	1600 - 4500	343 - 939	1,71

* Test Conditions:

ASHRAE LBP (Rated point): T. evap: -23.3°C / T. cond: 54.4°C

EN12900 MBP (Rated point): T. evap: -10°C / T. cond: 45°C

** Product still under testing. Preliminary performance demonstrated

For more detailed information, contact technical support



embraco.com

embraco
Nidec