

NEX



+ 24%* 冷量



+ 7%* 节能



+ 10%*



+ 30%* 减重



低噪音



高可靠性

NE平台排量从
NE平台排量扩
展到21cc



NE产品线实现本地化生产
本地生产和技术支持,
以提供最佳服务水平

*基于内部测试

think ahead

embraco
Nidec

主要应用



制冰机



服务柜



岛柜



展示柜

产品数据

型号	电压/频率	HP	排气量	电机	制冷剂	蒸发温度	测试工况	50Hz		60Hz	
								冷量 CAP [W]	能效 COP [W/W]	冷量 CAP [W]	能效 COP [W/W]
NEX2180UB	220-240V 50Hz	1	18,7	CSCR	R290	-40 to -10	ASHRAE LBP	929	1,59	-	-
NEU2178U	220-240V 50Hz	1	18,7	CSCR	R290	-40 to -10	ASHRAE LBP	905	1,52	-	-
NEX4170UA	115-127V 60Hz	1/2	16,8	CSCR	R290	-40 to 0	ARI LBP	-	-	789	1,34
NEX4180UA	115-127V 60Hz	1	18,7	CSCR	R290	-40 to 0	ARI LBP	-	-	891	1,31
NEU2178GK	220-240V 50Hz	1	16,8	CSCR	R404A	-40 to -10	ENI2900 LBP	501	1,14	-	-
NEU2183GKA	220-240V 50Hz	1	18,7	CSCR	R404A	-40 to -10	ENI2900 LBP	502	1,15	-	-
NEU2170UA	220-240V 50Hz	3/4	16,8	CSCR	R290	-40 to -10	ASHRAE LBP	820	1,54	-	-
NEX6217UA	220-240V 50Hz	3/4	14,3	CSCR	R290	-20 to 10	ENI2900 MBP	1071	2,09	-	-
NEX6225UA	220-240V 50Hz	1	21	CSCR	R290	-20 to 10	ENI2900 MBP	1612	2,07	-	-



embraco.com

think ahead

embraco
Nidec